

**I. PRODUCT AND COMPANY IDENTIFICATION**

Master Coating Technologies  
2777 Eagandale Boulevard  
Eagan, MN 55121

Information Phone: 1-800-765-6699  
Emergency Phone: 1-800-535-5053

DATE OF PREPARATION: November 26, 2007

SP203 Waterbased Drywall Primer (All Acrylic) (by Zolatone)

HMIS CODES  
Health 1  
Flammability 0  
Reactivity 0  
Personal Protection E

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

Ingredients	CAS#	Weight %	Exposure Limits		VP Mm Hg
			ACGIN/TLV	OSHA/PEL	
Oxygenated Hydrocarbon	25265-77-4	.44	N/A	N/A	N/A

ALL ingredients in this product are listed in the T.S.C.A. Inventory.

**3. HAZARDS IDENTIFICATION**

**ROUTES OF EXPOSURE**

INHALATION of vapor or spray mist.  
EYE or SKIN contact with the product, vapor or spray mist.

**EFFECTS OF OVEREXPOSURE**

EYES: Irritation.  
SKIN: Prolonged or repeated exposure may cause irritation.  
INHALATION: Vapors may irritate respiratory tract, cause headache or dizziness.  
SWALLOWED: May cause nausea

**4. FIRST AID MEASURES**



EYES: Flush eyes with water for 15 minutes. If irritation evident, see physician.  
SKIN: Wash affected area with soap and water, remove affected clothing  
INHALATION: Remove to fresh air. If breathing is difficult, give oxygen.  
SWALLOWED: Do not induce vomiting. If prolonged discomfort, see physician.

**5. FIREFIGHTING MEASURES**



Flammability Class: N/A Flash Point: N/A LEL: N/A UEL: N/A  
EXTINGUISHING MEDIA: Carbon dioxide, foam, dry chemical, water fog. Not a primary life hazard due to water  
SPECIAL FIREFIGHTING PROCEDURES: Use water fog to cool containers. Use self-contained breathing apparatus (SCRA). Not a primary fire source due to water content. Avoid spreading burning liquid with water used for cooling.  
UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapor is heavier than air. Vapors can be irritating to both eyes and skin. This product should not burn but may spatter if its temperature exceeds the boiling point. Closed containers may rupture when exposed to extreme heat. Do not expose these containers to heat, sparks or flame.

**6. ACCIDENTAL RELEASE MEASURES**

Steps to be taken in Case Material is Released or Spilled: Clean up with approved material. Wash area with water.  
Waste Disposal Method: Disposal should be done in accordance with prevailing regulations.

**7. HANDLING AND STORAGE**

STORAGE CATEGORY: N/A  
Do not allow material to freeze. (temperature below 32°F / 0°C)  
Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Respiratory Protection:** Maintain good ventilation. Exhaust at point of use recommended when needed to control exposure. To avoid breathing vapors or spray mist, open windows and doors. Ensure fresh air entry during application and drying.

**Ventilation:** Mechanical ventilation may be necessary during and after application.

**Protective Gloves:** Not usually required but, chemical resistant rubber or plastic preferred. Wear impervious gloves (Neoprene) to minimize skin contact.

**Eye Protection:** Safety glasses or goggles.

**Other Protective Equipment:** None

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Boiling Range:** 212° / 100°C

**Volatiles by Weight:** 46%

**Evaporation Rate:** Slower than n-Butyl Acetate

**Weight per Gallon:** 11.62 Pounds

**Vapor Density:** Heavier Than Air

**Spec. Gravity:** 1.40

**Liquid Density:** Heavier Than Water

**Appearance:** Opaque Liquid, Slight Odor

**Volatiles by Volume:** 66%

**VOC:** 66 grams per liter (0.55 lb/gal.)

## 10. STABILITY AND REACTIVITY

**Stability:** Stable

**Hazardous Polymerization:** Will not occur

**Incompatibility:** Peroxides and/or strong oxidizing agents.

**Conditions to Avoid:** Do not permit water reactive materials to mix with this product.

**Hazardous Decomposition Products:** Incomplete combustion may release carbon monoxide.

## 11. TOXICOLOGICAL INFORMATION

**CHRONIC HEALTH HAZARDS:** IARC Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

## 12. ECOLOGICAL INFORMATION

No data available.

## 13. DISPOSAL CONSIDERATIONS

Incinerate in an approved manner in an approved facility. Landfill in accordance with local, state and federal regulations. Dispose of in accordance with local regulations. Keep product out of sewers and waterways.

## 14. TRANSPORT INFORMATION

US Ground (DOT): Not Regulated    Canada (TDG): Not Regulated    IMO: Not Regulated

## 15. REGULATORY INFORMATION

**SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION:** No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

**CALIFORNIA PROPOSITION 65:** No ingredients in this product are subject Prop 65.

**TSCA CERTIFICATION:** All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

## 16. OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.